²⁰²³ MULE[™] 4000







POWER

Engine	4-stroke, 2-cylinder, OHV 90° V Liquid-cooled
Displacement	617cc
Maximum Torque	34.7 lb-ft @ 2,500 rpm
Bore x Stroke	2.99x2.68 in
Compression Ratio	10:3:1
Fuel System	DFI® with 34mm Mikuni throttle body
Transmission	Continuously Variable Transmission (CVT) with (H,N,R)
Final Drive	2WD, shaft. Dual mode rear differential with differential lock
Engine Braking	No
Alternator Output (max)	23 amp

Drum
7.5 in
6.3 gal
11.0 ft
46.3 x 51.6 x 11.4 in
800 lb
1,327 lb
2
1,200 lb
(2) Halogen headlights (2) tail/brake lights

116.7 in

CAPABILITY

	Front Suspension / Wheel Travel	MacPherson Strut/3.9 in	Overall Width	62.0 in
vv	wheet havet		Overall Height	75.8 in
	Rear Suspension / Wheel Travel	DeDion Axle/2.8 in	Curb Weight	1,338.4 lb*
	Front Tires	23x11.00-10	Wheelbase	73.6 in
	Rear Tires	23x11.00-10	Instruments	Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter
	Steering	Rack-and-pinion	Wheel Type	Steel
	Park Brake Type	Independent, Mechanical Drum	Color Choices	Dark Royal Red
	Front Brakes	Drum	color choices	Dark koyat keu
		Warranty	Kawasaki STRONG 3-Year Limited Warranty	

DETAILS

Overall Length





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULETM side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki-la.com for full product details.