
MULE PRO-FXT™ EPS LE









POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3,500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio 9.5:1

DFI® with 34mm throttle body **Fuel System**

Transmission

Final Drive

with differential lock

Engine Braking

Alternator Output 75 amp

Continuously Variable Transmission (CVT) with (H,L,N,R)

Selectable 2WD/4WD, shaft. Dual mode rear differential

Yes

(max)

CAPABILITY

Double wishbone/8.7 in Front Suspension / **Wheel Travel**

Rear Suspension / Wheel Travel

Rear Tires

Double wishbone/8.5 (L) /8.7 (R) in

Front Tires 26x9.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

26x11.00-12, radial

Park Brake Type Independent, Mechanical Disc

Front Brakes Dual Disc, 2 piston caliper

Rear Brakes Dual Disc, 1 piston caliper **Ground Clearance** 10.2 in

Turning Radius 16.0 ft

Cargo Bed 42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-Dimensions (LxWxH)

person)

7.9 gal

Cargo Bed Load 999 lb (3-person) / 350 lb (6-person) / 348 lb CA Model

Capacity

Fuel Capacity

Payload Capacity 1,616.3 lb / 1,263.5 lb CA Model

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2.000 lb

Lighting (2) Halogen headlights. (2) LED headlights

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 79.5 in

Curb Weight 1,922.8 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse

and parking indicators, seatbelt reminder lamps

Wheel Type Alloy

Additional Features

Color Choices Metallic Onyx Black, Metallic Sierra Blue

Kawasaki STRONG 3-Year Limited Warranty Warranty



