2024 JET SKI[®] ULTRA[®] 160LX-S





EBONY/CANDY STEEL FURNACE ORANGE



POWER

Engine	4-stroke, DOHC, four valves per cylinder, 4-cylinder inline	Lubrication
Displacement	1,498cc	Coupling Oil Capacity
Bore x Stroke	83.0 x 69.2mm	Fuel Capacity
Compression Ratio	10.6:1	Load Capacity
Induction	Naturally aspirated	Storage Capacity
Maximum Boost	N/A	
Cooling	Inducted water	DETAILS
System		Overall Length
Fuel System	DFI® with 60mm throttle body	Overall Width
Ignition	TCBI with Digital Advance	Overall Height
Starting System	Electric	Curb Weight
Propulsion System	155mm jet pump, axial-flow, single stage	Seating Capacity
Impeller	3-blade, oval-edge stainless steel	Color Choices
		Warranty

PERFORMANCE

Lubrication	Semi-dry sump system
Coupling	Direct drive from engine
Oil Capacity	5.8 qt
Fuel Capacity	21.1 gal
Load Capacity	496 lb
Storage Capacity	44.5 gal

	Overall Length	140.9 in
	Overall Width	47.0 in
	Overall Height	46.5 in
	Curb Weight	963.6 lb*
ge	Seating Capacity	3
	Color Choices	Ebony/Candy Steel Furnace Orange
	Warranty	12 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Ride responsibly. Kawasaki believes safety begins with us and continues with you. Always wear a USCG-approved personal flotation device, eyewear, gloves, footwear, and a wet suit or clothing that provides equivalent protection (board shorts with neoprene liner). Never ride under the influence of drugs or alcohol. Respect the rights of shoreline residents and other marine recreationists. Boat smart from the start. Take a Boating Safety course; for more information visit www.USCGBoating.org. Jet Ski watercraft are inboard powerboats and their use is subject to all applicable federal, state, and local boating laws. Read Owner's Manual and all on-product warnings. ©2024 Kawasaki Motors Corp., U.S.A.