KLX®230SM ABS







caliper and ABS

caliper and ABS

P	N	V	V	FI	R
	u	\mathbf{A}^{\prime}	٧ı	LI	М

Engine 4-stroke single, SOHC, air-cooled

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression

Ratio

Maximum Torque 13.2 lb-ft @ 6,400 rpm

Fuel System DFI® with dual 32mm throttle bodies

Ignition TCBI with Electronic Advance

9.4:1

Transmission 6-speed

Final Drive Sealed chain

Electronic Rider

Aids

DETAILS

Frame Type Perimeter, high-tensile steel

Rake/Trail 24.9°/3.0 in

Overall Length 80.1 in

Front Brakes

Rear Brakes

Overall Width 33.2 in

Overall Height 44.2 in

Ground 8.6 in Clearance

Seat Height

Curb Weight 299.8/302.0 lb* 50-State Model

33.0 in

Fuel Capacity 2.0 gal

Wheelbase 53.7 in

Smartphone Connectivity via RIDEOLOGY THE

Single 300mm petal disc with a dual-piston

Single 220mm petal disc with single-piston

APP MOTORCYCLE

Color Choices Battle Gray

Warranty 12 Month Limited Warranty

PERFORMANCE

Front
Suspension /
Wheel Travel

Rear Suspension
/ Wheel Travel

Uni-Trak® linkage system and single shock with adjustable spring preload/8.7 in

110/70-17

Anti-lock Brake System (ABS)

Scan with camera to view videos, key features and more.

Rear Tire



120/70-17