## **MULE**<sup>™</sup> 4010 4x4 FE







## **POWER**

Engine 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2,500 rpm

Bore x Stroke 2.99 x 2.68 in

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking N

Alternator Output 23 amp

(max)

Ground Clearance 6.9 in

Fuel Capacity 6.3 gal

Turning Radius 11.2 ft

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load

Capacity

Payload Capacity 1,312 lb

Seating Capacity 2

Towing Capacity 1,200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

46.3 x 51.6 x 11.4 in

800 lb

## CAPABILITY

Front Suspension / MacPherson Strut/3.9 in Wheel Travel

Rear Suspension / Wheel Travel

DeDion Axle/2.8 in

Front Tires 23x11.00-10

Rear Tires 23x11.00-10

Steering Rack-and-pinion w/ Electric Power Steering (EPS)

Park Brake Type

Independent, Mechanical Drum

Front Brakes Drum
Rear Brakes Drum

## **DETAILS**

Overall Length 116.7 in

Overall Width 62.0 in

Overall Height 78.1 in

Curb Weight 1,448.7 lb\*

Wheelbase 73.6 in

Instruments Parking brake warning light, coolant temperature

warning light, horn, 12V DC outlet, fuel gauge, hour

meter

Wheel Type Steel

Additional Features Roof, Horn, Universal Key, High Visibility Orange

Seatbelts

Color Choices Bright White

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

