## 2024 **MULE PRO-FXT<sup>™</sup> 1000 LE RANCH EDITION**





METALLIC TITANIUM

7.9 gal



## **POWER**

Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled, gas
Displacement	999cc
Maximum Torque	61.5 lb-ft
Bore x Stroke	92.0 x 75.1mm
<b>Compression Ratio</b>	10.1:1
Fuel System	DFI® with 38mm throttle body
Transmission	Continuously Variable Transmission (CVT) with (L,H,N,R)
Final Drive	Selectable 2WD/4WD, shaft Dual mode rear differential with differential lock
Engine Braking	Yes
Alternator Output (max)	90 amp

Turning Radius	16.0 ft
Cargo Bed Dimensions (LxWxH)	42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6- person)
Cargo Bed Load Capacity	999 lb (3-person) / 350 lb (6-person) / 348 lb CA Model
Payload Capacity	1,616.3 lb / 1,263.5 lb CA Model
Seating Capacity	3-person (1 row), 6 person (2 row)
Towing Capacity	2,000 lb
Lighting	(2) Halogen headlights. (2) LED headlights

## DETAILS

Fuel Capacity

Engine Braking		Yes			
	Alternator Output	90 amp	Overall Length	135.8 in	
	(max)		Overall Width	64.0 in	
CAPABILITY		Overall Height	80.9 in		
			Curb Weight	1,966.9 lb* / 1,969.1 lb* CA Model	
	Front Suspension / Wheel Travel	Double wishbone/11.0 in	Wheelbase	92.3 in	
	Rear Suspension / Wheel Travel	Double wishbone/10.1 in	Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning	
	Front Tires Rear Tires	26 x 9.00-12, radial 26 x 11.00-12, radial		indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt	
	Redi Tires	20 x 11.00-12, Taulat		reminder lamps	
	Steering	Electric Power Steering (EPS), Tilt steering			
	Park Brake Type	Independent, Mechanical Disc	Wheel Type	Alloy	
	Front Brakes	Dual Disc, 2 piston caliper	Additional Features	Roof, Additional Front Cup Holders, WARN® VRX 45 Winch, Premium Seats, Self-Leveling Rear Suspension	
	Rear Brakes	Dual Disc, 1 piston caliper	Color Choices	Metallic Titanium	
	Ground Clearance	12.6 in (max), 11.6 in (std)	Warranty	Kawasaki STRONG 3-Year Limited Warranty	





\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE<sup>TM</sup> side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki-la.com for full product details.