## TERYX KRX®4 1000 SE eS









## **POWER**

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 999cc

**Maximum Torque** 76.7 lb-ft @ 7,000 rpm

**Bore x Stroke** 92.0 x 75.1mm

**Compression Ratio** 11.5:1

DFI® with two 50mm throttle hodies **Fuel System** 

Ignition TCBI with Electronic Advance

**Starting System** 

**Transmission** Automatic CVT with centrifugal clutch (H,L,N,R)

Selectable 2WD/4WD with locking front differential, shaft **Final Drive** 

**Engine Braking** 

## DETAILS

Lighting

**Turning Radius** 

(LxWxH) **Cargo Bed Load** 

Capacity

**Payload Capacity** 

**Seating Capacity** 

**Towing Capacity** 

**Cargo Bed Dimensions** 

Ladder type, tubular steel

**Overall Length** 157.3 in **Overall Width** 68.1 in **Overall Height** 79.3 in

2,207.2 lb\* / 2,209.4 lb\* CA Model **Curb Weight** 

23.3 ft

351 lb

1,001 lb

N/A

14.6 x 33.1 x 9.1 in

Wheelbase 125 8 in

Multi-function digital meter with bar-style tachometer (2 Instruments display options), digital speedometer, bar-style fuel gauge,

(2) LED headlights, (2) LED taillights, LED stoplight

gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning

lamp, and CVT belt warning lamp.

**Wheel Type** Alloy wheels

**Additional Features** Roof, Hifonics® Bluetooth®/AM/FM Audio System, WARN® VRX

**Color Choices** Metallic Flat Raw Graystone Warranty 6 Month Limited Warranty

## CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and

KECS controlled compression damping/18.6 in

Rear Suspension / Wheel Travel

Steering

4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression

damping/21.1 in

**Front Tires** Maxxis® Carnivore 31 x 10.00R15 8PR **Rear Tires** 

Maxxis® Carnivore 31 x 10.00R15 8PR

Electric Power Steering (EPS) / rack-and-pinion

**Front Brakes** Dual hydraulic discs with two-piston calipers

Rear Brakes Dual hydraulic discs with single-piston calipers

Ground Clearance 14.4 in (max), 13.6 in (std)

**Fuel Capacity** 10.6 gal

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2024 Kawasaki Motors Corp., U.S.A.