²⁰²⁴ KLR[®]650 S





PEARL CRYSTAL WHITE/METALLIC CARBON GRAY





90/90-21

POWER

		Rear Tire	130/80-17
Engine	4-Stroke, single cylinder, DOHC	Front Brakes	Single 300mm disc with 2-piston calipers (and
Displacement	652cc		ABS)
Bore x Stroke	100.0 x 83.0mm	Rear Brakes	Single 240mm disc with single-piston caliper (and ABS)
Compression Ratio	9.8:1		
Maximum	39.1 lb-ft @ 4,500rpm	DETAILS	
Torque		Frame Type	Tubular, semi-double cradle
Fuel System	DFI® with 40mm throttle body	Rake/Trail	29.5°/4.6 in
Ignition	CDI	Overall Length	88.8 in
Transmission	5-speed, return shift with wet multi-disc manual clutch	Overall Width	38.2 in
Final Drive	Sealed chain	Overall Height	56.3/54.9 in (screen hi/lo)
Electronic Rider Aids	Anti-lock Brake System (ABS)	Ground Clearance	7.3 in
		Seat Height	32.1 in
DEDEODI			

Front Tire

PERFORMANCE

Front Suspension / Wheel Travel 41mm telescopic fork/ 6.7 in

Rear Suspension / Wheel Travel

Uni-Trak® single shock with adjustable rebound damping and adjustable spring preload/7.0 in

Overall Width	38.2 in
Overall Height	56.3/54.9 in (screen hi/lo)
Ground Clearance	7.3 in
Seat Height	32.1 in
Curb Weight	460.6 lb* (ABS), 456.2 lb* (non-ABS)
Fuel Capacity	6.1 gal
Wheelbase	59.6 in
Color Choices	Pearl Crystal White/Metallic Carbon Gray, Firecracker Red/Metallic Carbon Gray
Warranty	12 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki-la.com for full product details.