2024 **RIDGE[®] LIMITED HVAC**





METALLIC SHADOW GOLD

12.9 gal

15.0 ft

34.6 x 49.0 x 12.8 in

1,000/600 lb CA Model

1,499/1,100 lb CA Model

Ladder type, tubular steel

2,022.0/2,024.2 lb** CA Model

2,127.8/2,130.0 lb* CA Model

3, bench seat

All-LED lighting

2,500 lb

128.9 in

64.0 in

81.1 in

90.7 in

Fuel Capacity

Turning Radius

(LxWxH) Cargo Bed Load

Capacity **Payload Capacity**

Lighting

Frame **Overall Length**

Seating Capacity

Towing Capacity

DETAILS

Overall Width

Overall Height

Dry Weight

Curb Weight

Wheelbase

Cargo Bed Dimensions



POWER

| Engine | 4-stroke, DOHC, 4-valve In-Line Four-Cylinder, liquid-cooled | |
|----------------------------|--|--|
| Displacement | 999cc | |
| Maximum Horsepower | 92.0 hp1 @ 8,500 rpm | |
| Maximum Torque | 65.8 lb-ft @ 5,500 rpm | |
| Bore x Stroke | 73.4 x 59.0mm | |
| Compression Ratio | 10.6:1 | |
| Fuel System | EFI | |
| Ignition | TCBI with Digital Advance | |
| Starting System | Electric | |
| Transmission | Continuously Variable Transmission (CVT) with (H,L,N,R) | |
| Final Drive | Selectable 4WD with locking rear differential, shaft | |
| Engine Braking | Yes | |
| Alternator Output (max) | 85 amp | |
| Electronic Rider Aids | Power Modes, Economical Riding Indicator | |

CAPABILITY

| Front Suspension / Wheel Travel Rear Suspension / Wheel Travel | Long-Travel, Double Wishbone/12.7 in Long-Travel, Double Wishbone/12.7 in | Instruments | Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Bluetooth indicator, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and |
|---|--|---------------------|---|
| Front Tires | Duro 27 x 9-14 | | warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature) |
| Rear Tires | Duro 27 x 11-14 | Additional Features | 8" Garmin Tread®, WARN® VRX 45-S Powersport Winch, Full Cab with HVAC, Adjustable driver's seat, ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP Powersports, USB ports, KQR™ system compatible |
| Wheel Type | 14" Aluminum | | |
| Steering | Rack-and-pinion w/ Electric Power Steering (EPS) | | |
| Front Brakes | Dual hydraulic 249mm discs with two-piston calipers | Color Choices | Metallic Shadow Gold |
| Rear Brakes | Dual hydraulic 249mm discs with single-piston calipers | Warranty | Kawasaki STRONG 3-Year Limited Warranty |
| Ground Clearance | 12.6/13.6 in (max preload); 12.6 in CA Model | | |

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. Specifications subject to change. Visit Kawasaki-la.com for full product details.