

2025

VULCAN® 900 CLASSIC LT

Kawasaki
Let the Good Times Roll®



 METALLIC OCEAN BLUE/METALLIC MOONDUST GRAY



POWER

| | |
|-------------------|--|
| Engine | 4-stroke, 55-degree V-twin, liquid-cooled |
| Displacement | 903cc |
| Bore x Stroke | 88.0 x 74.2mm |
| Compression Ratio | 9.5:1 |
| Maximum Torque | 58.2 lb-ft @ 3,500 rpm |
| Fuel System | DFI® with 34mm throttle bodies (2), with sub-throttle valves |
| Ignition | TCBI with Electronic Advance |
| Transmission | 5-speed with positive neutral finder |
| Final Drive | Kevlar-reinforced belt |

| | |
|--------------|-----------------------------|
| Front Tire | 130/90-16 |
| Rear Tire | 180/70-15 |
| Front Brakes | Single 300mm hydraulic disc |
| Rear Brakes | Single 270mm hydraulic disc |

DETAILS

| | |
|------------------|--|
| Frame Type | Semi-double cradle, high-tensile steel |
| Rake/Trail | 32° / 6.3 in |
| Overall Length | 97.0 in |
| Overall Width | 39.6 in |
| Overall Height | 58.3 in |
| Ground Clearance | 5.3 in |
| Seat Height | 26.8 in |
| Curb Weight | 657.1 lb* |
| Fuel Capacity | 5.3 gal |
| Wheelbase | 64.8 in |
| Color Choices | Metallic Ocean Blue/Metallic Moondust Gray |
| Warranty | 24 Month Limited Warranty |

PERFORMANCE

| | |
|---------------------------------|--|
| Front Suspension / Wheel Travel | 41mm Showa telescopic fork/5.9 in |
| Rear Suspension / Wheel Travel | Uni-Trak® swingarm, 7-way adjustable spring preload/4.1 in |

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki-la.com for full product details.