2025 **VULCAN® 900 CLASSIC LT**





METALLIC OCEAN BLUE/METALLIC MOONDUST GRAY



POWER

Engine	4-stroke, 55-degree V-twin, liquid-cooled
Displacement	903cc
Bore x Stroke	88.0 x 74.2mm
Compression Ratio	9.5:1
Maximum Torque	58.2 lb-ft @ 3,500 rpm
Fuel System	DFI® with 34mm throttle bodies (2), with sub-throttle valves
Ignition	TCBI with Electronic Advance
Transmission	5-speed with positive neutral finder
Final Drive	Kevlar-reinforced belt

Front Tire 130/90-16 **Rear Tire** 180/70-15 Single 300mm hydraulic disc **Front Brakes** Single 270mm hydraulic disc **Rear Brakes**

DETAILS

9 3,500 rpm	Frame Type	Semi-double cradle, high-tensile steel
	Rake/Trail	32°/6.3 in
4mm throttle bodies (2), with e valves	Overall Length	97.0 in
lectronic Advance	Overall Width	39.6 in
h positive neutral finder	Overall Height	58.3 in
forced belt	Ground Clearance	5.3 in
	Seat Height	26.8 in
	Curb Weight	657.1 lb*
/a telescopic fork/5.9 in	Fuel Capacity	5.3 gal
	Wheelbase	64.8 in
wingarm, 7-way adjustable bad/4.1 in	Color Choices	Metallic Ocean Blue/Metallic Moondust Gray
	Warranty	24 Month Limited Warranty

PERFORMANCE

Front Suspension / Wheel Travel	41mm Showa te
Rear	Uni-Trak® swin
Suspension /	spring preload,

spring preloa

Scan with camera to view videos, key features and more.

Wheel Travel



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki-la.com for full product details.