

2025

# VULCAN® 900 CUSTOM

**Kawasaki**  
Let the Good Times Roll®



CANDY FIRE RED/EBONY



## POWER

<b>Engine</b>	4-stroke, 55-degree V-twin, liquid-cooled
<b>Displacement</b>	903cc
<b>Bore x Stroke</b>	88.0 x 74.2mm
<b>Compression Ratio</b>	9.5:1
<b>Maximum Torque</b>	58.2 lb-ft @ 3,500 rpm
<b>Fuel System</b>	DFI® with 34mm throttle bodies (2), with sub-throttle valves
<b>Ignition</b>	TCBI with Electronic Advance
<b>Transmission</b>	5-speed with positive neutral finder
<b>Final Drive</b>	Kevlar-reinforced belt

<b>Front Tire</b>	80/90-21
<b>Rear Tire</b>	180/70-15
<b>Front Brakes</b>	Single 300mm hydraulic disc
<b>Rear Brakes</b>	Single 270mm hydraulic disc

## DETAILS

<b>Frame Type</b>	Semi-double cradle, high-tensile steel
<b>Rake/Trail</b>	33° / 7.2 in
<b>Overall Length</b>	94.7 in
<b>Overall Width</b>	35.2 in
<b>Overall Height</b>	44.1 in
<b>Ground Clearance</b>	5.5 in
<b>Seat Height</b>	27.0 in
<b>Curb Weight</b>	610.8 lb*
<b>Fuel Capacity</b>	5.3 gal
<b>Wheelbase</b>	64.8 in
<b>Color Choices</b>	Candy Fire Red/Ebony
<b>Warranty</b>	12 Month Limited Warranty

## PERFORMANCE

<b>Front Suspension / Wheel Travel</b>	41mm Showa telescopic fork/5.9 in
<b>Rear Suspension / Wheel Travel</b>	Uni-Trak® swingarm, 7-way adjustable spring preload/4.1 in

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki-la.com](http://Kawasaki-la.com) for full product details.