## <sup>2025</sup> **KLX®110R L**







### POWER

Engine 4-stroke	e, single-cylinder, SOHC, air-cooled
Displacement 112cc	
Bore x Stroke 53.0 x 50	D.6mm
Compression 9.5:1 Ratio	
	B18 carburetor and screw type limiter on grip housing
Ignition DC-CDI	
Transmission 4-speed manual	l, return shift, wet multi-disc clutch
Final Drive Chain	

# Front Tire2.50 x 14Rear Tire3.00 x 12Front Brakes90mm mechanical drum, cable actuatedRear Brakes110mm mechanical drum, rod actuated

#### DETAILS

/pe	Frame Type	Backbone frame, high-tensile steel
, , , , , , , , , , , , , , , , , , , ,	Rake/Trail	24.2°/1.9 in
	<b>Overall Length</b>	61.4 in
2	Overall Width	25.6 in
	Overall Height	39.0 in
	Ground Clearance	10.4 in
	Seat Height	28.7 in
in	Curb Weight	167.5 lb*
	Fuel Capacity	1.0 gal
ck/5.2	Wheelbase	42.3 in
	Color Choices	Lime Green, Battle Gray
	Warranty	6 Month Limited Warranty

### PERFORMANCE

Front Suspension / Wheel Travel	30mm hydraulic telescopic fork/5.5 in
Rear Suspension / Wheel Travel	Swingarm with single hydraulic shock/5.2 in

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki-la.com for full product details.