KLX®300









caliper

POWFR

Engine 4-stroke single, DOHC, liquid-cooled

Displacement 292cc

Bore x Stroke 78.0 x 61.2mm

Compression

Ratio

11.1:1

Fuel System DFI® with 34mm Keihin throttle body

Ignition CDI

Transmission 6-speed, return shift with wet multi-disc

manual clutch

Final Drive Chain

Rear Tire 4.6 x 18 Front Brakes Single 250mm petal disc with a dual-piston caliper Rear Brakes Single 240mm petal disc with single-piston

DETAILS

Frame Type	Tubular, Semi Double Cradle
Rake/Trail	26.7° / 4.2 in
Overall Length	85.6 in
Overall Width	32.3 in
Overall Height	46.7 in
Ground	10.8 in

Seat Height 35.2 in

Clearance

Curb Weight 302.1 lb*

Fuel Capacity 2.0 gal

Wheelbase 56.7 in

Color Choices Lime Green, Battle Gray, Cypher Camo Gray

(Matte)

Warranty 12 Month Limited Warranty

PERFORMANCE

Front
Suspension /
Wheel Travel

43mm inverted cartridge fork with adjustable compression damping /10.0 in

Rear Suspension / Wheel Travel Uni-Trak® gas charged shock with piggyback reservoir with adjustable compression, rebound damping and spring

preload/9.1 in

Front Tire 3.00 x 21



