## <sup>2025</sup> **KX™85**







POWER		Front Brakes	Single 220mm petal disc with dual-piston caliper
Engine	2-stroke, single-cylinder with exhaust power valve (KIPS), liquid-cooled	Rear Brakes	Single 184mm petal disc with single-piston caliper
Displacement	84cc	DETAILS	
Bore x Stroke	48.5 x 45.8mm		
Compression Ratio	10.9:1 (low speed) / 9.0:1 (high speed)	Frame Type	High-tensile steel perimeter design with subframe member
Fuel System	28mm Keihin carburetor	Rake/Trail	29.0°/3.8 in
Ignition	CDI with Digital Advance	Overall Length	72.0 in
Transmission	6-speed, return shift, with wet multi-disc	Overall Width	30.1 in
	manual clutch	Overall Height	43.3 in
Final Drive	Chain	Ground Clearance	11.4 in
		Clearance	
PERFORMANCE		Seat Height	32.7 in
Front	36mm inverted telescopic cartridge fork	Curb Weight	164.4 lb*
Suspension / Wheel Travel	with 20-way compression damping/10.8 in	Fuel Capacity	1.32 gal
Rear	Uni-Trak® single shock system with 24-way	Wheelbase	49.8 in
Suspension / Wheel Travel	compression and 21-way rebound damping, plus adjustable spring preload/10.8 in	Special Features	ERGO-FIT®
Front Tire	70/100-17	Color Choices	Lime Green
Rear Tire	90/100-14	Warranty	Not Available

## Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki-la.com for full product details.