MULE PRO-FX™ 1000 HD EDITION







P	N	۱	N	F	R
	u		м	L	

4-stroke, 2-cylinder, DOHC, liquid-cooled, gas **Engine**

999cc Displacement

Maximum Torque 61.5 lb-ft @ 4,500 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 10.1:1

DFI® with 38mm throttle body **Fuel System**

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Selectable 2WD/4WD, shaft. Dual mode rear differential with **Final Drive**

differential lock

Engine Braking

Alternator Output 90 amp

(max)

Ground Clearance 11.9 in (max), 11.8 in (std)

Fuel Capacity 7.9 gal **Turning Radius** 16.0 ft

Cargo Bed Dimensions 54.1 x 53.3 x 11.0 in

(LxWxH)

Cargo Bed Load

Capacity

999/600 lb CA Model

Payload Capacity 1.616.3/1.263.5 lb CA Model

Seating Capacity

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights, (2) LED headlights

CAPABILITY

Front Suspension / Double wishbone/11.0 in Wheel Travel

Rear Suspension /

Double wishbone/10.1 in

Wheel Travel

Front Tires

26 x 9-12, radial

Rear Tires 26 x 11-12, radial

Wheel Type Steel

Rack-and-pinion Steering

Park Brake Type

Independent, mechanical disc

Front Brakes

Dual disc, 2-piston caliper

Rear Brakes Dual disc, 1-piston caliper

DETAILS

Overall Length 136.6 in **Overall Width** 64.0 in **Overall Height** 81.1 in

1,816.9/1,819.1 lb** CA Model **Dry Weight**

1,891.9/1,894.1 lb* CA Model **Curb Weight**

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel gauge,

odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt

reminder lamps

Additional Features Roof, Rear Bumper, Additional Under Seat Storage Bin,

Rearview Mirror, Hydraulic Cargo Bed Lift, Self-Leveling Rear

Suspension, Anti-cinch Seatbelts

Color Choices Firecracker Red

Kawasaki STRONG 3-Year Limited Warranty Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki-la.com for full product details.