NINJA® ZX™-10RR ABS









Horizontal back-link with Showa Balance Free Rear

damping, fully adjustable spring preload/4.5 in

mounted monobloc 4-piston calipers, Kawasaki

Intelligent anti-lock Brake System (KIBS)

Cushion (BFRC) lite shock, stepless, dual-range (low-/ high-speed) compression damping, stepless rebound

Brembo dual semi-floating 330mm discs with dual radial

Single 220mm disc with aluminum single-piston caliper,

Kawasaki Intelligent anti-lock Brake System (KIBS)

POWER

Engine 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-

cooled

Displacement 998cc

Bore x Stroke 76.0 x 55.0mm

Compression Ratio

Maximum Torque 81.7 lb-ft @ 11,500 rpm

DFI®, 47mm throttle bodies and Variable Air Intake **Fuel System**

System (VAI)

Ignition TCBI with digital advance

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider

Δids

Öhlins Electronic Steering Damper, Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Sport-Kawasaki TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management Function (KCMF), Power Modes

(Full/Mid/Low)

DETAILS

Overall Length

Rear Brakes

Rear Suspension /

Wheel Travel

Front Tire

Rear Tire

Front Brakes

Aluminum perimeter **Frame Type**

120/70 ZR17

190/55 ZR17

25.0°/4.1 in

82.1 in

Rake/Trail

Overall Width 29.5 in

Overall Height 46.7 in

Ground Clearance 5.3 in

Seat Height 32.9 in

456.4 lb* **Curb Weight**

Fuel Capacity 4.5 gal

Wheelbase 57.1 in

Special Features 4.3" Full-Color TFT Instrumentation, Smartphone

Connectivity via RIDEOLOGY THE APP

Color Choices Metallic Matte Graphenesteel Gray

12 Month Limited Warranty Warranty

PERFORMANCE

Front Suspension / **Wheel Travel**

43mm inverted Showa Balance Free Fork (BFF). adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in



