ALL-NEW 2025 RIDGE[®] CREW HVAC





CANDY PERSIMMON RED

12.9 gal

19.0 ft

2,500 lb

155.3 in

64.0 in

81.5 in

122.2 in

All-LED lighting

34.6 x 49.0 x 12.8 in

1,000/600 lb CA Model

1,444/1,290 lb CA Model

6-person (2 row), bench seats

Ladder type, tubular steel

2,368.2/2,370.4 lb** CA Model

2,478.4/2,480.6 lb* CA Model



POWER

Engine	4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled
Displacement	999cc
Maximum Horsepower	92.0 hp1 @ 8,500 rpm
Maximum Torque	65.8 lb-ft @ 5,500 rpm
Bore x Stroke	73.4 x 59.0mm
Compression Ratio	10.6:1
Fuel System	EFI
Ignition	TCBI with Digital Advance
Starting System	Electric
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 4WD with locking rear differential, shaft
Engine Braking	Yes
Alternator Output (max)	85 amp
Electronic Rider Aids	Power Modes, Economical Riding Indicator

CAPABILITY

	Front Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in	Instruments	Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil
	Rear Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in		change reminder, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery,
	Front Tires	Duro 27 x 9-14		EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature)
	Rear Tires	Duro 27 x 11-14	Additional Features	Full Cab with HVAC, Adjustable driver's seat, ERGO-FIT®, Full-color
	Wheel Type	14" Aluminum		TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP Powersports, USB ports, KQR™ system compatible
	Steering	Rack-and-pinion w/ Electric Power Steering (EPS)	Color Choices	Candy Persimmon Red
	Front Brakes	Dual hydraulic 249mm discs with two-piston calipers	Warranty	Kawasaki STRONG 3-Year Limited Warranty
	Rear Brakes	Dual hydraulic 249mm discs with single-piston calipers		
	Ground Clearance	13.2/13.8 in (max preload); 13.2 in CA Model		

Fuel Capacity

Turning Radius

(LxWxH) Cargo Bed Load

Capacity Payload Capacity

Seating Capacity

Towing Capacity Lighting

DETAILS

Overall Width

Overall Height

Dry Weight

Curb Weight

Wheelbase

Frame Overall Length

Cargo Bed Dimensions





RE

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 'This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. Specifications subject to change. Visit Kawasaki-la.com for full product details.