



# NUEVA 2025 Z900 ABS

**Kawasaki**  
Let the Good Times Roll®



-  METALLIC SPARK BLACK/METALLIC CARBON GRAY/EBONY
-  GALAXY SILVER/METALLIC SPARK BLACK/PHANTOM BLUE



## POTENCIA

Motor	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled
Cilindrada	948cc
Diámetro por carrera	73.4 x 56.0mm
Relación de compresión	11.8:1
Maximum Horsepower	123.0 hp <sup>1</sup> @ 9,500 rpm
Par motor máximo	73.1 lb-ft @ 7,700 rpm
Sistema de combustible	DFI® with 36mm throttle bodies
Encendido	TCBI with Electronic Advance
Transmisión	6-speed, return shift
Transmisión final	Sealed chain
Asistencia electrónica para el piloto	Economical Riding Indicator, Electronic Cruise Control, Kawasaki Traction Control (KTRC), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-Enhanced Chassis Orientation Awareness

Neumático trasero	180/55-17
Frenos delanteros	Dual 300mm semi-floating discs with radial-mount 4-piston calipers and ABS
Frenos traseros	Single 250mm disc with single-piston caliper and ABS

## DETALLES

Tipo de chasis	Trellis, high tensile steel
Ángulo de dirección/Avance	24.7° / 4.3 in
Largo total	81.3 in
Ancho total	32.7 in
Altura del asiento	43.3 in
Distancia al suelo	5.7 in
Altura del asiento	31.9 in
Dry Weight	423.4 lb** / 425.6 lb** 50-State Model
Peso en orden de marcha	467.5 lb* / 469.7 lb* 50-State Model
Depósito de combustible	4.5 gal
Distancia entre ejes	57.1 in
Características especiales	5" All-digital TFT color instrumentation, All-LED lighting, ERGO-FIT®, Smartphone Connectivity with Voice Command and Turn-by-Turn Navigation via RIDEOLGY THE APP MOTORCYCLE
Colores disponibles	Metallic Spark Black/Metallic Carbon Gray/Ebony, Galaxy Silver/Metallic Spark Black/Phantom Blue
Garantía	12 Month Limited Warranty

## RENDIMIENTO

Suspensión delantera/recorrido del neumático	41mm inverted telescopic fork with rebound damping and spring preload adjustability/4.7 in
Suspensión trasera/recorrido del neumático	Horizontal back-link, gas-charged rear shock with rebound damping and spring preload adjustability/5.5 in
Neumático delantero	120/70-17

Escanear con cámara para ver videos, características clave y más.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visite [Kawasaki-la.com](http://Kawasaki-la.com) para obtener detalles completos del producto.