

NUEVA 2025

# NINJA® 1100SX ABS

**Kawasaki**  
Let the Good Times Roll®



GRIS METALLIC CARBON/NEGRO METALLIC DIABLO



## POTENCIA

|                                       |  |
|---------------------------------------|--|
| Motor                                 | 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled  |
| Cilindrada                            | 1,099cc  |
| Diámetro por carrera                  | 77.0 x 59.0mm  |
| Relación de compresión                | 11.8:1   |
| Maximum Horsepower                    | 134.0 hp <sup>1</sup> @ 9,000 rpm  |
| Par motor máximo                      | 83.2 lb-ft @ 7,600 rpm   |
| Sistema de combustible                | DFI® with 38mm Electronic Throttle Valves  |
| Encendido                             | TCBI with Digital Advance  |
| Transmisión                           | 6-speed, return shift with wet multi-disc manual Assist & Slipper Clutch   |
| Transmisión final                     | Sealed chain   |
| Asistencia electrónica para el piloto | Economical Riding Indicator, Electronic Cruise Control, Kawasaki TRaction Control (KTRC), Kawasaki Intelligent anti-lock Brake System (KIBS), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-Enhanced Chassis Orientation Awareness |

## RENDIMIENTO

|  |  |
|--|--|
| Suspensión delantera/recorrido del neumático | 41mm inverted telescopic Showa fork with compression and rebound damping, adjustable spring preload/4.7 in   |
| Suspensión trasera/recorrido del neumático   | Horizontal back-link, gas-charged rear shock with rebound damping, remotely adjustable spring preload/5.6 in |

|                     |   |
|---------------------|---|
| Neumático delantero | 120/70-17   |
| Neumático trasero   | 190/50-17   |
| Frenos delanteros   | Dual 300mm discs with radial-mount 4-piston monobloc calipers, Kawasaki Intelligent anti-lock Brake System (KIBS) |
| Frenos traseros     | Single 260mm disc with single-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS)                  |

## DETALLES

|                            |   |
|----------------------------|---|
| Tipo de chasis             | Twin-spar aluminum  |
| Ángulo de dirección/Avance | 24.0° /3.9 in   |
| Largo total                | 82.7 in   |
| Ancho total                | 31.7 in   |
| Altura del asiento         | 46.9 in/48.2 in w/ windshield high  |
| Distancia al suelo         | 5.3 in  |
| Altura del asiento         | 32.3 in   |
| Dry Weight                 | 471.9 lb**  |
| Peso en orden de marcha    | 518.2 lb*   |
| Depósito de combustible    | 5.0 gal   |
| Distancia entre ejes       | 56.7 in   |
| Características especiales | 4.3" All-digital TFT Instrumentation, All-LED lighting, USB Type-C outlet, Smartphone Connectivity with Voice Command via RIDEOLGY THE APP MOTORCYCLE |
| Colores disponibles        | Metallic Carbon Gray/Metallic Diablo Black  |

Escanear con cámara para ver videos, características clave y más.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visite [Kawasaki-la.com](http://Kawasaki-la.com) para obtener detalles completos del producto.