

2025

# NINJA<sup>®</sup> ZX<sup>™</sup> -14R ABS

**Kawasaki**  
Let the Good Times Roll<sup>®</sup>



METALLIC MATTE SOVEREIGN RED/METALLIC FLAT SPARK BLK/  
METALLIC MATTE GRAPHITE GRY



## POTENCIA

Motor	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled
Cilindrada	1,441cc
Diámetro por carrera	84.0 x 65.0mm
Relación de compresión	12.3:1
Maximum Horsepower	197.0 hp <sup>1</sup> @ 10,000 rpm
Par motor máximo	116.5 lb-ft @ 7,500 rpm
Sistema de combustible	DFI <sup>®</sup> with 44mm Mikuni throttle bodies (4)
Encendido	TCBI with Electronic Advance
Transmisión	6-speed, return shift
Transmisión final	Sealed chain
Asistencia electrónica para el piloto	Economical Riding Indicator, Kawasaki TRaction Control (KTRC) (3-mode), Power Modes, Anti-lock Brake System (ABS)

## RENDIMIENTO

Suspensión delantera/recorrido del neumático	43mm inverted cartridge fork with adjustable preload, 18-way compression and 15-way rebound damping adjustment/4.6 in
--	---

Suspensión trasera/recorrido del neumático	Bottom-link Uni-Trak <sup>®</sup> and gas-charged shock with adjustable preload, stepless rebound and compression damping adjustments, adjustable ride height/4.9 in
Neumático delantero	120/70-17
Neumático trasero	190/50-R17
Frenos delanteros	Dual 310mm semi-floating Brembo discs with dual radial-mounted Brembo 4-piston M50 monobloc calipers and ABS
Frenos traseros	Single 250mm disc with twin-piston caliper and ABS

## DETALLES

Tipo de chasis	Aluminum monocoque
Ángulo de dirección/Avance	23.0°/3.7 in
Largo total	85.4 in
Ancho total	30.3 in
Altura del asiento	46.1 in
Distancia al suelo	4.9 in
Altura del asiento	31.5 in
Peso en orden de marcha	593.1 lb*
Depósito de combustible	5.8 gal
Distancia entre ejes	58.3 in
Colores disponibles	Metallic Matte Sovereign Red/Metallic Flat Spark Black/Metallic Matte Graphite Gray
Garantía	12 Month Limited Warranty

Escanear con cámara para ver videos, características clave y más.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visite [Kawasaki-la.com](http://Kawasaki-la.com) para obtener detalles completos del producto.