

NUEVA 2025

RIDGE® CREW HVAC CAMO





 TRUETIMBER® STRATA



| POTENCIA | | | |
|---|--|---|---|
| Motor | 4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled | Radio de giro | 19.0 ft |
| Cilindrada | 999cc | Dimensiones de la plataforma de carga (L x An x Al) | 34.6 x 49.0 x 12.8 in |
| Maximum Horsepower | 92.0 hp¹ @ 8,500 rpm | Capacidad de la plataforma de carga | 1,000/600 lb CA Model |
| Par motor máximo | 65.8 lb-ft @ 5,500 rpm | Capacidad de carga útil | 1,444/1,290 lb CA Model |
| Diámetro por carrer | 73.4 x 59.0mm | Asientos | 6-person (2 row), bench seats |
| Relación de compresión | 10.6:1 | Capacidad de remolque | 2,500 lb |
| Sistema de combustible | EFI | Faros | All-LED lighting |
| Ignition | TCBI with Digital Advance | DETALLES | |
| Arranque | Electric | | |
| Transmisión | Continuously Variable Transmission (CVT) with (H,L,N,R) | Cuadro | Ladder type, tubular steel |
| Transmisión final | Selectable 4WD with locking rear differential, shaft | Largo total | 155.3 in |
| Frenado del motor | Yes | Ancho total | 64.0 in |
| Alternator Output (max) | 85 amp | Altura total | 81.5 in |
| Electronic Rider Aids | Power Modes, Economical Riding Indicator | Dry Weight | 2,368.2/2,370.4 lb** CA Model |
| CAPACIDAD | | Peso en orden de marcha | 2,478.4/2,480.6 lb* CA Model |
| Suspensión delantera/ recorrido del neumático | Long-Travel, Double Wishbone/12.7 in | Distancia entre ejes | 122.2 in |
| Suspensión trasera/ recorrido del neumático | Long-Travel, Double Wishbone/12.7 in | Instrumental | Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature) |
| Neumáticos delanteros | Duro 27 x 9-14 | Características adicionales | Full Cab with HVAC, Adjustable driver's seat, ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDELOGY THE APP Powersports, USB ports, QQR™ system compatible |
| Neumáticos traseros | Duro 27 x 11-14 | Colores disponibles | TRUETIMBER® STRATA |
| Wheel Type | 14" Aluminum | Garantía | Kawasaki STRONG 3-Year Limited Warranty |
| Dirección | Rack-and-pinion w/ Electric Power Steering (EPS) | | |
| Frenos delanteros | Dual hydraulic 249mm discs with two-piston calipers | | |
| Frenos traseros | Dual hydraulic 249mm discs with single-piston calipers | | |
| Distancia al suelo | 13.2/13.8 in (max preload); 13.2 in CA Model | | |
| Depósito de combustible | 12.9 gal | | |

Escanear con cámara para ver videos, características clave y más.





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
Specifications subject to change. Visite [Kawasaki-la.com](https://www.kawasaki-la.com) para obtener detalles completos del producto.