



NUEVA 2025

RIDGE® XR DELUXE HVAC

Kawasaki
Let the Good Times Roll®



-  GRIS ICE
-  METALLIC GRAYSTONE



POTENCIA

| | |
|-------------------------|--|
| Motor | 4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled |
| Cilindrada | 999cc |
| Maximum Horsepower | 116.0 hp ¹ @ 8,500 rpm |
| Par motor máximo | 73.8 lb-ft @ 8,000 rpm |
| Diámetro por carrer | 73.4 x 59.0mm |
| Relación de compresión | 10.6:1 |
| Sistema de combustible | EFI |
| Ignition | TCBI with Digital Advance |
| Arranque | Electric |
| Transmisión | Continuously Variable Transmission (CVT) with (H,L,N,R) |
| Transmisión final | Selectable 4WD with locking front/rear differential, shaft |
| Frenado del motor | Yes |
| Alternator Output (max) | 85 amp |
| Electronic Rider Aids | Power Modes, Economical Riding Indicator |

CAPACIDAD

| | |
|--|--|
| Suspensión delantera/ recorrido del neumático | Long-Travel, Double Wishbone/12.7 in |
| Suspensión trasera/ recorrido del neumático | Long-Travel, Double Wishbone/12.7 in |
| Neumáticos delanteros | Duro 30 x 10-14 |
| Neumáticos traseros | Duro 30 x 10-14 |
| Wheel Type | 14" Aluminum |
| Dirección | Rack-and-pinion w/ Electric Power Steering (EPS) |
| Frenos delanteros | Dual hydraulic 249mm discs with two-piston calipers |
| Frenos traseros | Dual hydraulic 249mm discs with single-piston calipers |
| Distancia al suelo | 13.8/14.6 in (max preload); 13.8 in CA Model |
| Depósito de combustible | 12.9 gal |

| | |
|---|-----------------------|
| Radio de giro | 15.0 ft |
| Dimensiones de la plataforma de carga (L x An x Al) | 34.6 x 49.0 x 12.8 in |
| Capacidad de la plataforma de carga | 1,000/600 lb CA Model |
| Capacidad de carga útil | 1,275/875 lb CA Model |
| Asientos | 3, bench seat |
| Capacidad de remolque | 2,500 lb |
| Faros | All-LED lighting |

DETALLES

| | |
|--------------------------------|---|
| Cuadro | Ladder type, tubular steel |
| Largo total | 125.4 in |
| Ancho total | 64.0 in |
| Altura total | 82.3 in |
| Dry Weight | 1,964.7/1,966.9 lb** CA Model |
| Peso en orden de marcha | 2,070.5/2,072.7 lb* CA Model |
| Distancia entre ejes | 90.7 in |
| Instrumental | Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature) |
| Características adicionales | Full Cab with HVAC, Adjustable driver/passenger seats, ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDELOGY THE APP Powersports, USB ports, KQR™ system compatible |
| Colores disponibles | Ice Gray, Metallic Graystone |
| Garantía | Kawasaki STRONG 3-Year Limited Warranty |

Escanear con
cámara para ver
videos, característi-
cas clave y más.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
 Specifications subject to change. Visite Kawasaki-la.com para obtener detalles completos del producto.